

Seat Belt for Forklift

Forklift Seat Belt - Described in the Regulation guidelines are the use of seatbelts and operator restraints on forklifts. It says that the accountability falls on the employers' to be able to ensure that each machine, piece of equipment and tool is used correctly according to the instructions of the producer.

In regards to their inspection, fabrication, use, design and maintenance Rough Terrain forklifts have to meet the regulations of ANSI Standard ASME B56.6-1992.

Mobile equipment like side boom tractors with a Rollover Protective Structure (ROPS), need to contain seat belts which meet the Society of Automotive Engineers safety requirements; Society of Automotive Engineers Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whatever mobile machine includes seat belts required by law, the operator and subsequent passengers need to make sure they use the belts every time the vehicle is in motion or engaged in operation since this can cause the machine to become unstable and hence, not safe.

If a seat belt or other driver restraint is required on a lift truck.

The seat belt requirements while operating a forklift depend on various factors. Whether the forklift is equipped along with a Rollover Protective Structure, the kind of forklift itself and the year the forklift was actually manufactured all add to this determination. The manufacturer's instructions and the requirements of the applicable standard are referenced in the Regulation.

In the case of powered industrial trucks, ANSI Standard ASME B56.1-1993 refers to an operator restraint device, enclosure or system. A driver restraint device, enclosure or system is designed so as to assist the driver in reducing the risk of entrapment of the torso and/or head between the truck and the ground in the event of a tip over. The system or restraint device might comprise a seat belt, though a seat belt is not necessarily a part of such equipment or system.